EVELINO

BONDS THAT LAST, SHINE THAT SURPASS

**TECHNICAL DATA SHEET**

REF: TDS-EVL-LASTIC
ISSUE: SEPTEMBER 2026 | VERSION 2.1




TILES SOLUTIONS

# Evelino Lastic – Two-Component Elastomeric Adhesive

### PRODUCT OVERVIEW

Lastic is what we recommend when the substrate itself isn't rigid — timber floors, plywood, metal panels, drywall — surfaces that expand, contract or flex in ways a standard cement adhesive can't handle. It's a two-part system: cementitious powder mixed with an acrylic latex copolymer, curing into a flexible, fully waterproof bond that can absorb several millimetres of movement without letting go. It's also non-reactive with moisture-sensitive stones like green marble, so it's a safe choice for natural stone on dynamic surfaces.

## KEY FEATURES & PERFORMANCE ADVANTAGES

- S2 deformability — absorbs up to 5mm of substrate movement
- Fully waterproof — works for pool linings and wet installations
- Bonds to wood, plywood, metal, drywall, cement board and existing tile
- Two-part acrylic latex system for flexibility without losing strength
- Handles vibration and shear stress on substrates prone to movement
- Safe on moisture-sensitive natural stone, including green marble

## TECHNICAL SPECIFICATIONS & PERFORMANCE DATA

| PARAMETER / PROPERTY | SPECIFICATION / VALUE |
|---|---|
| **Packaging / Pack Size** | 15 kg Kit (Powder Pack + Liquid Copolymer Admix) |
| **Estimated Coverage** | Approx. 35–45 sq.ft per kit at 3mm applied bed thickness |
| **Deformability Standard** | S2 (e 5 mm) |
| **Application Temperature** | +5°C to +30°C |
| **Pot Life / Work Time** | 45–60 minutes after mixing |
| **Shelf Life / Storage** | 12 months — stored off-floor in cool, dry conditions |

## APPLICATION GUIDELINES & SITE PRECAUTIONS

### SURFACE PREPARATION & MIXING

Substrate must be structurally sound, dry, flat, and free of laitance, oil, grease, or loose debris. Mix thoroughly according to product technical directions. Use clean tools and potable water or hardener as specified.

### STORAGE & ENVIRONMENTAL CONDITIONS

Apply in ambient temperatures between +5°C and +35°C. Avoid direct harsh sunlight and rain during application and initial cure. Store in original sealed containers in a cool, dry place off concrete floors.

### HEALTH & OCCUPATIONAL SAFETY

Wear suitable protective gloves, safety goggles, and respiratory masks during mixing and application. In case of contact with eyes or skin, wash immediately with plenty of clean water and seek medical advice.



Disclaimer: The technical recommendations and application instructions provided are based on our present state of scientific and practical knowledge. Since site conditions, substrate quality, and workmanship are beyond our direct control, the user must test the suitability of the product for the intended application. Evelino Technology reserves the right to modify specifications without prior notice.